



EASY 2K WOOD FLOOR FINISH



SPECIFICATIONS

VOC.	>212 g/L
Solids.	34%
Flash Point.	>100° F
Solvents.	Water/Glycol Ether
Shelf Life	1 Year Unopened
Coverage	450 sq. ft./gal
Color	Clear

FEATURES

- No Lap Marks
- Clear Finish
- UV Inhibitor
- Easy to Apply
- Aluminum Oxide
- 15 Year Warranty

CLEAR FLOOR FINISH FOR ALL HARDWOODS

Absco™ Easy 2K Wood Floor Finish combines the latest developments in wood floor finishes to deliver fortified durability using aluminum oxide and a two component 100% urethane formulation. And its Advanced No Lap Technology makes it easy to apply and results in a clear, even finish. The Professional's Choice for over 40 years, Absco™ is manufactured from the highest quality resins. For interior use only.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NAWFA or NOFMA accepted manner. Make several passes with the sandpaper, increasing the paper fineness with each pass. The final pass before application of Absco Easy 2K should be with a #100 grit screen disc or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth. The floor, product and room temperature should be at least 65 degrees F.

SURFACE PREPARATION: Previously Finished Floors: Remove old finish in poor condition completely. All wax, grease, soaps and dirt must be removed thoroughly. For floors in good condition, screen the floor #120 to #150 Screen disc, or #180 grit sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth.

AVAILABLE IN: HIGH GLOSS, SATIN, SEMI-GLOSS, AND MATTE FINISHES in one-gallon containers only.