

EASY 2K Wood Floor Finish

PROFESSIONAL POLYURETHANE CLEAR FLOOR FINISH FOR ALL HARDWOODS



Absco™ Easy 2K Wood Floor Finish combines the latest developments in wood floor finishes to deliver fortified durability using aluminum oxide and a two component 100% urethane formulation. And its Advanced No Lap Technology makes it easy to apply and results in a clear, even finish. The Professional's Choice for over 40 years, Absco™ is manufactured from the highest quality resins. For interior use only.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NWWA or NOFMA accepted manner. Make several passes with the sandpaper, increasing the paper fineness with each pass. The final pass before application of Absco MAX should be with a #100 grit screen disc or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth. The floor, product and room temperature should be at least 65 degrees F.

Previously Finished Floors: Remove old finish in poor condition completely. All wax, grease, soaps and dirt must be removed thoroughly. For floors in good condition, screen the floor #120 to #150 Screen disc, or #180 grit sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth.

SPECIFICATIONS

VOC <275g/L
Solids 43%
Flash Point >100° F
Solvents Mineral Spirits
Shelf Life 1 Year Unopened
Coverage 450 sq. ft/gal
Color Clear

FEATURES

- > No Lab Marks
- > Clear Finish
- > UV Inhibitor
- > Easy to Apply
- > Aluminum Oxide
- > 15 Year Warranty

AVAILABLE IN: HIGH GLOSS, SATIN, SEMI-GLOSS, AND MATTE FINISHES in one-gallon containers only.

AbsoluteCoatings.com

OFFICE (732) 821-3200
 FAX (732) 821-8180
 999 Elizabeth Street
 North Brunswick, NJ 08902



EASY 2K Wood Floor Finish

PROFESSIONAL POLYURETHANE CLEAR FLOOR FINISH FOR ALL HARDWOODS



Absco™ Easy 2K Wood Floor Finish combines the latest developments in wood floor finishes to deliver fortified durability using aluminum oxide and a two component 100% urethane formulation. And its Advanced No Lap Technology makes it easy to apply and results in a clear, even finish. The Professional's Choice for over 40 years, Absco™ is manufactured from the highest quality resins. For interior use only.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NWWFA or NOFMA accepted manner. Make several passes with the sandpaper, increasing the paper fineness with each pass. The final pass before application of Absco MAX should be with a #100 grit screen disc or sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth. The floor, product and room temperature should be at least 65 degrees F.

Previously Finished Floors: Remove old finish in poor condition completely. All wax, grease, soaps and dirt must be removed thoroughly. For floors in good condition, screen the floor #120 to #150 Screen disc, or #180 grit sandpaper. Remove dust completely by sweeping, vacuuming and wiping the floor with a lightly dampened lint free cloth.

ESPECIFICACIONES

COV <275 g/L
 Sólidos..... 43%
 Punto de inflamación..... >100° F
 Solventes..... Alcoholes minerales
 Vida útil..... 1 año en recipient
 Cobertura 450 pies cuadrados/gal
 Color..... Ámbar

CARACTERÍSTICAS

- > No Lab Marks
- > Clear Finish
- > UV Inhibitor
- > Easy to Apply
- > Aluminum Oxide
- > 15 Year Warranty

DISPONIBLE EN: HIGH GLOSS, SATIN, SEMI-GLOSS, AND MATTE FINISHES in one-gallon containers only.

AbsoluteCoatings.com

OFICINA (732) 821-3200
 FAX (732) 821-8180
 999 Elizabeth Street
 North Brunswick, NJ 08902

