

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 1 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

SECTION 1: Identification

Product identifier

Product name: Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Product code: 98918

Recommended use of the product and restriction on use

Relevant identified uses: Finishes, Coatings, and Related Materials

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Absolute Coatings

1999 Elizabeth Street

North Brunswick , New Jersey 089026316

(732)821-3200

Emergency telephone number:

United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 4

Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H227 Combustible liquid

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P280 Wear protective gloves/protective clothing/eye protection/face protection

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P271 Use only outdoors or in a well-ventilated area

P370+P378 In case of fire: Use ... to extinguish

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 2 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

P302+P352 IF ON SKIN: Wash with plenty of water/ ...
P333+P313 If skin irritation or rash occurs: Get medical advice/attention
P321 Specific treatment (see ... on this label)
P363 Wash contaminated clothing before reuse
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 Call a POISON CENTER/doctor/.../if you feel unwell
P403+P235 Store in a well-ventilated place. Keep cool
P403+P233 Store in a well-ventilated place. Keep container tightly closed
P405 Store locked up
P501 Dispose of contents/container to...

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 822-06-0	Hexamethylene diisocyanate	<0.2
CAS number: 28182-81-2	Hexamethylene diisocyanate, oligomers	<70
CAS number: N/A	Blocked Hexane, 1,6-diisocyanato-, homopolymer	<30
CAS number: 111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	<40

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 3 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate medical attention and special treatment

Specific treatment:

Effects are dependent on exposure (dose, concentration, contact time).

If respiratory symptoms persist, seek medical attention.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Combustible liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 4 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 5 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Hexamethylene diisocyanate	822-06-0	REL: 0.04 mg/m ³
	Hexamethylene diisocyanate	822-06-0	Ceiling Limit: 0.02 ppm
	Hexamethylene diisocyanate	822-06-0	Ceiling Limit: 0.14 mg/m ³
United States(California)	Hexamethylene diisocyanate	822-06-0	PEL: 0.034 mg/m ³ (0.005 ppm)
ACGIH	Hexamethylene diisocyanate	822-06-0	TWA: 0.005 ppm

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear liquid
Odor	Mild
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 6 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Initial boiling point/range	N/A
Flash point (closed cup)	65°C
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	N/A
Vapor pressure	For HDI Polyisocyanate= 4.7X10 ⁻⁷ mmHg@ 20°C (68°F)
Vapor density	N/A
Density	1.05 +/- 0.02 g/cc
Relative density	1.05 +/- 0.02
Solubilities	Insoluble, reacts slowly with water
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Hexamethylene diisocyanate	oral	LD50 Rat: 959 mg/m ³ (Manganese neodecanoate)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 7 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Name	Route	Result
Hexamethylene diisocyanate, oligomers	inhalation	LC50 Rat: 18,500 mg/m ³ (1 Hr)
Blocked Hexane, 1,6-diisocyanato-, homopolymer	oral	LD50 Rat: >2000 mg/kg
	inhalation	LC50 Rat: 0.39 mg/L (4 hours)
	dermal	LD50 Rabbit: >2000 mg/kg
1-methoxy-3-(3-methoxypropoxy)propane	dermal	LD50 Rat: >2000 mg/kg
	inhalation	LC50 Rat: >792 ppmV
	oral	LD50 Rat: 3075 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Hexamethylene diisocyanate	Causes severe skin burns and eye damage.
1-methoxy-3-(3-methoxypropoxy)propane	Causes serious eye irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:

Name	Result
Hexamethylene diisocyanate	May cause an allergic skin reaction.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Hexamethylene diisocyanate, oligomers	May cause an allergic skin reaction.
Blocked Hexane, 1,6-diisocyanato-, homopolymer	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Hexamethylene diisocyanate, oligomers	Not Applicable

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 8 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

National Toxicology Program (NTP):

Name	Classification
Hexamethylene diisocyanate, oligomers	Not Applicable

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation.

Product data:

No data available.

Substance data:

Name	Result
Blocked Hexane, 1,6-diisocyanato-, homopolymer	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 9 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Name	Result
Blocked Hexane, 1,6-diisocyanato-, homopolymer	LC50 Danio rerio: 17.8 mg/L (96 hours)
	EC50 Daphnia magna: 58 mg/L (48 hours)
1-methoxy-3-(3-methoxypropoxy)propane	LC50 Poecilia reticulata: >891 mg/L (96 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
1-methoxy-3-(3-methoxypropoxy)propane	LC50 Oncorhynchus mykiss: >300 mg/L (14 days)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Hexamethylene diisocyanate	Not readily biodegradable.
Blocked Hexane, 1,6-diisocyanato-, homopolymer	Not readily biodegradable.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Hexamethylene diisocyanate	This substance does not have a high bioaccumulation potential.
1-methoxy-3-(3-methoxypropoxy)propane	BCF: 138

Mobility in soil

Product data: No data available.

Substance data: No data available.

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB..

Substance data:

PBT assessment:

Hexamethylene diisocyanate	Substance is not PBT.
1-methoxy-3-(3-methoxypropoxy)propane	Substance is not PBT.

vPvB assessment:

Hexamethylene diisocyanate	Substance is not vPvB.
1-methoxy-3-(3-methoxypropoxy)propane	Substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 10 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

Disposal methods:


Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:


Not determined or not applicable.

SECTION 14: Transport information


United States Transportation of dangerous goods (49 CFR DOT)

UN number	UN 2478, Flammable, Toxic N.O.S
UN proper shipping name	Isocyanate solution
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	UN 2478, Flammable, Toxic N.O.S
UN proper shipping name	Isocyanate solution
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 2478, Flammable, Toxic N.O.S
UN proper shipping name	Isocyanate solution
UN transport hazard class(es)	3 
Packing group	III
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 11 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

822-06-0	Hexamethylene diisocyanate	Not Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Listed

Export notification under TSCA Section 12(b):

822-06-0	Hexamethylene diisocyanate	Not Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
N/A	Blocked Hexane, 1,6-diisocyanato-, homopolymer	Not Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Listed

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

822-06-0	Hexamethylene diisocyanate	Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Not Listed

CERCLA:

822-06-0	Hexamethylene diisocyanate	Listed	100 Lbs
----------	----------------------------	--------	---------

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

822-06-0	Hexamethylene diisocyanate	Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
N/A	Blocked Hexane, 1,6-diisocyanato-, homopolymer	Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Not Listed

New Jersey Right to Know:

822-06-0	Hexamethylene diisocyanate	Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
N/A	Blocked Hexane, 1,6-diisocyanato-, homopolymer	Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Not Listed

New York Right to Know:

822-06-0	Hexamethylene diisocyanate	Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Not Listed

Pennsylvania Right to Know:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.16.2020

Page 12 of 12

Easy 2K Waterborne Premium Wood Floor Finish Satin & Matte Hardener

822-06-0	Hexamethylene diisocyanate	Not Listed
28182-81-2	Hexamethylene diisocyanate, oligomers	Not Listed
N/A	Blocked Hexane, 1,6-diisocyanato-, homopolymer	Listed
111109-77-4	1-methoxy-3-(3-methoxypropoxy)propane	Not Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-2-1

HMIS: 2*-2-1

Initial preparation date: 06.16.2020

Revision Notes:

Revision Date	Notes
2020-05-07	Version 07

End of Safety Data Sheet