

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 1 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

SECTION 1: Identification

Product identifier

Product name: LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Product code: 54801

Recommended use of the product and restriction on use

Relevant identified uses: Finishes, Coatings, and Related Materials

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Absolute Coatings

1999 Elizabeth Street

North Brunswick , New Jersey 089026316

(732)821-3200

Emergency telephone number:

United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Eye irritation, category 2A

Reproductive toxicity, category 1B

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H315 Causes skin irritation

H319 Causes serious eye irritation

H360 May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Precautionary statements:

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 2 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P321 Specific treatment (see ... on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention

P362 Take off contaminated clothing and wash it before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container to...

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 112926-00-8	Silica gel, precipitated, crystalline free	<1.5
CAS number: 872-50-4	1-methyl-2-pyrrolidone	<2
CAS number: 1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	<1
CAS number: 34590-94-8	(2-Methoxymethylethoxy)propanol	<6

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 3 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 4 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Silica gel, precipitated, crystalline free	112926-00-8	TWA: 10 mg/m ³ (ACGIH TLV)
	(2-Methoxymethylethoxy)propanol	34590-94-8	8-Hour TWA: 100 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	15-Minute STEL: 150 ppm
OSHA	Silica gel, precipitated, crystalline free	112926-00-8	TWA: 6 mg/m ³ (Table Z-1-A)
	Silica gel, precipitated, crystalline free	112926-00-8	8-Hour TWA: 0.8 mg/m ³ (Table Z-3)
	(2-Methoxymethylethoxy)propanol	34590-94-8	TWA: 100 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	TWA: 600 mg/m ³
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 150 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 900 mg/m ³
NIOSH	Silica gel, precipitated, crystalline free	112926-00-8	REL: 6 mg/m ³ (10 hr)
	Silica gel, precipitated, crystalline free	112926-00-8	IDLH: 3000 mg/m ³
	(2-Methoxymethylethoxy)propanol	34590-94-8	REL: 100 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	REL: 600 mg/m ³
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 150 ppm
	(2-Methoxymethylethoxy)propanol	34590-94-8	STEL: 900 mg/m ³

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 5 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	(2-Methoxymethylethoxy)propanol	34590-94-8	IDLH: 600 ppm
WEEL	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 10 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 40 mg/m ³
United States(California)	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 1 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 4 mg/m ³

Biological limit values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	1-methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	End of shift	100 mg/L

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Milky liquid
Odor	Mild
Odor threshold	Not determined or not available.
pH	7.5 - 9

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 6 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Melting point/freezing point	Not determined or not available.
Initial boiling point/range	100°C
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Miscible with water
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible materials:

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Silica gel, precipitated, crystalline free	oral	LD50 Mouse: > 15,000 mg/kg
1-methyl-2-pyrrolidone	oral	LD50 Rat: 4150 mg/kg
	inhalation	LC50 Rat: >5.1 mg/L (4 hours)
	dermal	LD50 Rat: >5000 mg/kg

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 7 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Silica gel, precipitated, crystalline free	Group 3

National Toxicology Program (NTP):

Name	Classification
Silica gel, precipitated, crystalline free	Not Applicable

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment:

May damage fertility or the unborn child.

Product data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 8 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Substance data:

Name	Result
1-methyl-2-pyrrolidone	May damage fertility or the unborn child (developmental effects).

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	LC50 Oncorhynchus mykiss: 500 mg/L (96 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	NOEC Daphnia magna: 12.5 mg/L (21 days)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Readily biodegradable.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 9 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

Name	Result
(2-Methoxymethylethoxy)propanol	Readily biodegradable in water.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Low potential for bioaccumulation.

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
1-methyl-2-pyrrolidone	Adsorption to the solid soil phase is not expected.

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB..

Substance data:

PBT assessment:

1-methyl-2-pyrrolidone	Substance is not PBT.
------------------------	-----------------------

vPvB assessment:

1-methyl-2-pyrrolidone	Substance is not vPvB.
------------------------	------------------------

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 10 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

112926-00-8	Silica gel, precipitated, crystalline free	Not Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

112926-00-8	Silica gel, precipitated, crystalline free	Not Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	Not Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Not Listed

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

112926-00-8	Silica gel, precipitated, crystalline free	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	Not Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.18.2020

Page 11 of 11

LNL 500X Residential Grade Waterborne Wood Floor Finish Semi-Gloss Part A

New Jersey Right to Know:

112926-00-8	Silica gel, precipitated, crystalline free	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	Not Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

New York Right to Know:

112926-00-8	Silica gel, precipitated, crystalline free	Not Listed
872-50-4	1-methyl-2-pyrrolidone	Not Listed
1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	Not Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

Pennsylvania Right to Know:

112926-00-8	Silica gel, precipitated, crystalline free	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
1053241-44-3	Poly (oxy-1,2-ethanediyl), alpha-hydro-omega-hydroxy-, mono (C16-18 and C18-unsatd. alkyl) ethers, diester with N-[3-carboxyamino]methyl]-3,5,5-trimethylcyclohexyl]carbamic acid	Not Listed
34590-94-8	(2-Methoxymethylethoxy)propanol	Listed

California Proposition 65:

⚠ WARNING: This product can expose you to 1-methyl-2-pyrrolidone; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-0-0

HMIS: 2*-0-0

Initial preparation date: 06.18.2020

Revision Notes:

Revision Date	Notes
2020-06-18	Version 03

End of Safety Data Sheet