

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 1 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

### SECTION 1: Identification

#### Product identifier

**Product name:** Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

**Product code:** Satin : 99101 -99105 - Semi-Gloss 99201- 99205

#### Recommended use of the product and restriction on use

**Relevant identified uses:** Not determined or not applicable.

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

Absolute Coatings

1999 Elizabeth Street

North Brunswick , New Jersey 089026316

(732)821-3200

#### Emergency telephone number:

##### United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

### SECTION 2: Hazard(s) identification

#### GHS classification:

Reproductive toxicity, category 2

#### Label elements

##### Hazard pictograms:



**Signal word:** Warning

#### Hazard statements:

H361 Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

#### Precautionary statements:

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P280 Wear protective gloves/protective clothing/eye protection/face protection

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container to...

**Hazards not otherwise classified:** None

### SECTION 3: Composition/information on ingredients

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 2 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

Identification	Name	Weight %
CAS number: 15956-58-8	2-ethylhexanoic acid, manganese salt	<0.9
CAS number: 112945-52-5	Silica, amorphous, fumed, cryst.-free	<2
CAS number: 29911-28-2	1-(2-butoxy-1-methylethoxy)propan-2-ol	<3
CAS number: 109-86-4	2-methoxyethanol	<0.09
CAS number: 110-80-5	2-ethoxyethanol	<0.09

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Show this Safety Data Sheet to the doctor in attendance.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

#### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 3 of 12

### Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

Treat symptomatically.

#### SECTION 5: Firefighting measures

##### Extinguishing media

###### Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

###### Unsuitable extinguishing media:

Do not use water jet.

##### Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

##### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

##### Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

#### SECTION 6: Accidental release measures

##### Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

##### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

##### Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

##### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

#### SECTION 7: Handling and storage

##### Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

##### Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

#### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 4 of 12

### Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	2-ethylhexanoic acid, manganese salt	15956-58-8	REL: 1 mg/m <sup>3</sup> (for up to a 10-hour workday during a 40-hour workweek)
	2-ethylhexanoic acid, manganese salt	15956-58-8	STEL: 3 mg/m <sup>3</sup>
	2-ethylhexanoic acid, manganese salt	15956-58-8	IDLH: 500 mg/m <sup>3</sup>
	Silica, amorphous, fumed, cryst.-free	112945-52-5	REL: 6 mg/m <sup>3</sup>
	Silica, amorphous, fumed, cryst.-free	112945-52-5	IDLH: 3000 mg/m <sup>3</sup>
	2-methoxyethanol	109-86-4	IDLH: 200 ppm
	2-methoxyethanol	109-86-4	REL: 0.3 mg/m <sup>3</sup> (0.1 ppm [10-hour workday])
	2-ethoxyethanol	110-80-5	IDLH: 500 ppm
OSHA	2-ethylhexanoic acid, manganese salt	15956-58-8	PEL Ceiling: 5 mg/m <sup>3</sup>
	Silica, amorphous, fumed, cryst.-free	112945-52-5	8-Hour TWA: 0.8 mg/m <sup>3</sup>
	2-methoxyethanol	109-86-4	PEL: 80 mg/m <sup>3</sup> (25 ppm)
	2-methoxyethanol	109-86-4	TWA: 80 mg/m <sup>3</sup> (25 ppm)
	2-ethoxyethanol	110-80-5	8-Hour TWA-PEL: 200 ppm
United States(California)	2-ethylhexanoic acid, manganese salt	15956-58-8	8-Hour TWA: 0.2 mg/m <sup>3</sup> (as Mn)
	2-methoxyethanol	109-86-4	PEL: 16 mg/m <sup>3</sup> (5 ppm)
	2-methoxyethanol	109-86-4	REL: 93 ug/m <sup>3</sup> (Acute Inhalation)
	2-methoxyethanol	109-86-4	REL: 60 ug/m <sup>3</sup> (Chronic Inhalation)
	2-ethoxyethanol	110-80-5	8-Hour TWA-PEL: 5 ppm
	2-ethoxyethanol	110-80-5	REL: 370 ug/m <sup>3</sup> (Acute inhalation)
	2-ethoxyethanol	110-80-5	REL: 70 ug/m <sup>3</sup> (Chronic inhalation)
ACGIH	2-methoxyethanol	109-86-4	TLV-TWA: 0.1 ppm
	2-ethoxyethanol	110-80-5	TLV-TWA: 5 ppm

#### Biological limit values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-methoxyethanol	109-86-4	2-Methoxyacetic acid	Creatinine in urine	End of shift at end of work week	1 mg/g
	2-methoxyethanol	109-86-4	2-Methoxyacetic acid	Creatinine in urine	End of shift at end of work week.	1 mg/g
	2-ethoxyethanol	110-80-5	2-Ethoxyacetic acid	Creatinine in urine	End of shift at end of work week	100 mg/g

#### Information on monitoring procedures:

Not determined or not applicable.

#### Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 5 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

equivalent).

### Personal protection equipment

#### Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

#### Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

### General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Milky -Amber
<b>Odor</b>	Mild
<b>Odor threshold</b>	N/A
<b>pH</b>	8 -9
<b>Melting point/freezing point</b>	Not Available
<b>Initial boiling point/range</b>	Not Available
<b>Flash point (closed cup)</b>	> 93 °C
<b>Evaporation rate</b>	Not Available
<b>Flammability (solid, gas)</b>	Not Flammable
<b>Upper flammability/explosive limit</b>	Not Available
<b>Lower flammability/explosive limit</b>	Not Available
<b>Vapor pressure</b>	Not Available
<b>Vapor density</b>	Not Available
<b>Density</b>	8.51 lb/gal
<b>Relative density</b>	1.02 +/- 0.02
<b>Solubilities</b>	Miscible with water
<b>Partition coefficient (n-octanol/water)</b>	Not Available
<b>Auto/Self-ignition temperature</b>	Not Available
<b>Decomposition temperature</b>	Not Available
<b>Dynamic viscosity</b>	Not Available
<b>Kinematic viscosity</b>	Not Available
<b>Explosive properties</b>	Not Available

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 6 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

<b>Oxidizing properties</b>	Not Available
-----------------------------	---------------

### Other information

<b>VOC (g/l)</b>	275 g/l
------------------	---------

## SECTION 10: Stability and reactivity

### Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical stability:

Stable under recommended handling and storage conditions.

### Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

### Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

### Incompatible materials:

None known.

### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

### Substance data:

Name	Route	Result
Silica, amorphous, fumed, cryst.-free	oral	LD50 Rat: 3160 mg/kg
1-(2-butoxy-1-methylethoxy)propan-2-ol	dermal	LD50 Rat: >2000 mg/kg
	oral	LD50 Rat: 3700 mg/kg
2-methoxyethanol	oral	LD50 Rat: 2257 mg/kg
	inhalation	LC50 Rat: >5000 ppmV (4 hours)
	dermal	LD50 Rabbit: 1280 mg/kg
2-ethoxyethanol	oral	LD50 Rat: 2125 mg/kg
	inhalation	LC50 Rat: 7.36 mg/L (8 hours)
	dermal	LD50 Rabbit: 3300 mg/kg

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

### Product data:

No data available.

### Substance data:

Name	Result
2-ethylhexanoic acid, manganese salt	Causes skin irritation.
Silica, amorphous, fumed, cryst.-free	Causes skin irritation.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 7 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
2-ethylhexanoic acid, manganese salt	Causes serious eye irritation.
Silica, amorphous, fumed, cryst.-free	Causes serious eye irritation.

### Respiratory or skin sensitization

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Carcinogenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

#### International Agency for Research on Cancer (IARC):

Name	Classification
Silica, amorphous, fumed, cryst.-free	Group 3
2-methoxyethanol	Not Applicable
2-ethoxyethanol	Not Applicable

#### National Toxicology Program (NTP):

Name	Classification
Silica, amorphous, fumed, cryst.-free	Not Applicable
2-methoxyethanol	Not Applicable
2-ethoxyethanol	Not Applicable

**OSHA Carcinogens:** Not applicable

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:**

Suspected of damaging fertility or the unborn child.

**Product data:**

No data available.

**Substance data:**

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 8 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

Name	Result
2-ethylhexanoic acid, manganese salt	Suspected of damaging the unborn child (oral exposure).
2-methoxyethanol	May damage fertility. May damage the unborn child.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Silica, amorphous, fumed, cryst.-free	May cause respiratory irritation.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
2-ethylhexanoic acid, manganese salt	May cause damage to nervous system through prolonged or repeated exposure via inhalation.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

**Other information:**

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Result
1-(2-butoxy-1-methylethoxy)propan-2-ol	LC50 Poecilia reticulata: 841 mg/L (96 hours)
	EC50 Daphnia magna: >1000 mg/L (48 hours)
2-methoxyethanol	LC50 Lepomis macrochirus: 10000 mg/L (96 hours)
2-ethoxyethanol	LC50 Lepomis macrochirus: 10000 mg/L (96 hours)
	EC50 Daphnia magna: 10000 mg/L (48 hours)

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 9 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

**Product data:** No data available.

**Substance data:**

Name	Result
2-ethylhexanoic acid, manganese salt	NOEC Daphnia magna: 25 mg/L (21 d)
2-methoxyethanol	NOEC Fish: 2 472 mg/L (30 days)
2-ethoxyethanol	NOEC Dap: >100 mg/L (21 days)

### Persistence and degradability

**Product data:** No data available.

**Substance data:**

Name	Result
2-ethylhexanoic acid, manganese salt	Readily biodegradable (99% degradation after 28 days).
1-(2-butoxy-1-methylethoxy)propan-2-ol	Readily biodegradable
2-methoxyethanol	Readily biodegradable (88% degradation after 20 days).
2-ethoxyethanol	Readily biodegradable.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:**

Name	Result
2-ethoxyethanol	Log Pow: 0.32

### Results of PBT and vPvB assessment

**Product data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

**Substance data:**

**PBT assessment:**

1-(2-butoxy-1-methylethoxy)propan-2-ol	This substance is not PBT.
2-methoxyethanol	Substance is not PBT.
2-ethoxyethanol	Substance is not PBT.

**vPvB assessment:**

1-(2-butoxy-1-methylethoxy)propan-2-ol	This substance is not vPvB.
2-methoxyethanol	Substance is not vPvB.
2-ethoxyethanol	Substance is not vPvB.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 10 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not Regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not Regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

## SECTION 15: Regulatory information

### United States regulations

**Inventory listing (TSCA):** All ingredients are listed-active or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

### Export notification under TSCA Section 12(b):

15956-58-8	2-ethylhexanoic acid, manganese salt	Not Listed
112945-52-5	Silica, amorphous, fumed, cryst.-free	Not Listed
29911-28-2	1-(2-butoxy-1-methylethoxy)propan-2-ol	Not Listed
109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Not Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 11 of 12

## Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

**SARA Section 313 toxic chemicals:**

109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Listed

**CERCLA:**

110-80-5	2-ethoxyethanol	Listed	1000
----------	-----------------	--------	------

**RCRA:**

110-80-5	2-ethoxyethanol	Listed	U359
----------	-----------------	--------	------

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

**Massachusetts Right to Know:**

112945-52-5	Silica, amorphous, fumed, cryst.-free	Listed
109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Listed

**New Jersey Right to Know:**

15956-58-8	2-ethylhexanoic acid, manganese salt	Listed
109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Listed

**New York Right to Know:**

15956-58-8	2-ethylhexanoic acid, manganese salt	Listed
109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Listed

**Pennsylvania Right to Know:**

15956-58-8	2-ethylhexanoic acid, manganese salt	Listed
112945-52-5	Silica, amorphous, fumed, cryst.-free	Listed
109-86-4	2-methoxyethanol	Listed
110-80-5	2-ethoxyethanol	Listed

**California Proposition 65:**

**⚠️WARNING:** This product can expose you to chemicals including 2-methoxyethanol and 2-ethoxyethanol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

**Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 1-1-0

**HMIS:** 1\*-1-0

**Initial preparation date:** 01.27.2021

**Revision Notes:**

Revision Date	Notes
---------------	-------

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.27.2021

Page 12 of 12

**Absco Grand NXTGEN Oil•n•H2O Wood Floor Finish**

2020-11-16

VERSION : 1.0

### Additional information:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Absolute Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Absolute Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

**End of Safety Data Sheet**