



PROFESSIONAL POLYURETHANE 275 VOC WOOD FLOOR FINISH



SPECIFICATIONS:

VOC.....	<275 g/L
Solids.....	39% - 41%
Flash Point.....	> 101°F (> 38°C)
Solvent	Mineral Spirits
Viscosity.....	80 - 180 cps
Odor	Solvent Like
Coverage.....	500 sq. ft/gal
Dry Time:.....	4 - 8 Hours
Color (Wet).....	Slightly Milky
Color (Dry).....	Amber Clear
Sheens.....	Super High Gloss, Semi-Gloss, Satin, Matte
Sizes	1g & 5g Containers

FEATURES

- Great Coverage & Low Odor
- Beautifies and Protects
- 275 VOC Formulation is Compliant Nationally
- Application Tracking Technology for Easy Application
- High Solids
- Commercial and Residential Use

Find us in

MasterSpec[®]

a product of The American Institute of Architects



NEW! PROVEN QUALITY AND VALUE WITH CONSISTENT RESULTS IN A NATIONALLY VOC COMPLIANT FORMULA

Absco Professional Polyurethane Wood Floor Finish makes it easy, with great coverage, easy application and multiple VOC formulations. Its oil-modified high solids formulation is durable, self-leveling and is formulated for beauty and protection. And this 275 VOC formula is compliant nationally, features Application Tracking Technology and is designed for residential and commercial use.

Please refer to the product label for specific surface preparation and application instructions.