

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 1 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

SECTION 1: Identification

Product Identifier

Product Name: Absco Quick Dry Penetrating Wood Finish - Espresso

Product code: 30731, 30734

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Finishes, Coatings, and Related Materials0

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Canlak Coatings

1999 Elizabeth Street

North Brunswick, New Jersey 089026316

(732)821-3200

<https://canlakcoatings.com>

Emergency Telephone Number:

United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2

Eye irritation, category 2A

Flammable liquids, category 3

Skin sensitization, category 1

Respiratory sensitization, category 1

Carcinogenicity, category 2

Reproductive toxicity, category 1B

Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 2 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

- H226 Flammable liquid and vapor
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H317 May cause an allergic skin reaction
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H351 Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H360 May damage fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H336 May cause drowsiness or dizziness

Precautionary Statements:

- P264 Wash skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P272 Contaminated work clothing must not be allowed out of the workplace
- P284 Wear respiratory protection
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P271 Use only outdoors or in a well-ventilated area
- P302+P352 IF ON SKIN: Wash with plenty of water/ ...
- P321 Specific treatment (see ... on this label)
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362 Take off contaminated clothing and wash it before reuse
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P337+P313 If eye irritation persists: Get medical advice/attention
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P370+P378 In case of fire: Use ... to extinguish
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention
- P363 Wash contaminated clothing before reuse
- P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/ ...
- P308+P313 IF exposed or concerned: Get medical advice/attention
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P312 Call a POISON CENTER/doctor/.../if you feel unwell
- P403+P235 Store in a well-ventilated place. Keep cool
- P405 Store locked up
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 3 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Identification	Name	Weight %
CAS Number: 64742-47-8	Distillates (petroleum), hydrotreated light	<45
CAS Number: 8052-41-3	Stoddard Solvent with < 0.1% Benzene content	<15
CAS Number: 123-42-2	2-Pentanone, 4-hydroxy-4-methyl-	<3
CAS Number: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	<2
CAS Number: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<2
CAS Number: 22464-99-9	Zirconium 2-Ethylhexanoate	<1
CAS Number: 136-52-7	Cobalt bis(2-ethylhexanoate)	<1
CAS Number: 108-88-3	Toluene	<0.5
CAS Number: 14808-60-7	Silica, crystalline quartz (respirable)	<0.3
CAS Number: 8007-24-7	Cashew nutshell liquid	<0.2
CAS Number: 872-50-4	1-methyl-2-pyrrolidone	<0.2
CAS Number: 96-29-7	Methyl ethyl ketoxime	<0.2

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If exposed, seek medical advice/attention.

After Skin Contact:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 4 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Product is flammable. Exposure to sources of ignition may cause physical injury.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation exposure may cause allergy, asthma symptoms or breathing difficulties. Symptoms may include cough, chronic phlegm, shortness of breath, wheezing and chest tightness. Symptoms may be delayed.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Long term exposure may affect fertility. Symptoms include, but are not limited to: menstrual problems, altered sexual behavior/fertility/ and pregnancy outcome. Long term exposure may also affect development of the unborn child. Symptoms include, but are not limited to: intrauterine growth retardation, pre-term birth, birth defects and postnatal death.

Suspected of causing cancer. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Overexposure via inhalation requires urgent medical treatment.

Skin/eye burns require immediate treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 5 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 6 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Zirconium 2-Ethylhexanoate	22464-99-9	8-Hour TWA: 5 mg/m ³ (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	15-Minute STEL: 10 mg/m ³ (as Zr)
	Toluene	108-88-3	TWA: 20 ppm
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	8-Hour TWA: 50 ppm
	Silica, crystalline quartz (respirable)	14808-60-7	8-Hour TWA: 0.025 mg/m ³ (respirable fraction)
	Distillates (petroleum), hydrotreated light	64742-47-8	TLV-TWA: 200 mg/m ³ (Kerosene and jet-fuels [non-aerosol], as total hydrocarbon vapor)
NIOSH	Zirconium 2-Ethylhexanoate	22464-99-9	REL: 5 mg/m ³ (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	STEL: 10 mg/m ³ (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	IDLH: 25 mg/m ³ (as Zr)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 7 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Toluene	108-88-3	REL-TWA: 375 mg/m ³ (100 ppm [up to 10 hr])
	Toluene	108-88-3	STEL: 560 mg/m ³ (150 ppm)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	Ceiling Limit: 1800 mg/m ³ (15-min)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	IDLH: 20000 mg/m ³
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	REL: 350 mg/m ³
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	TWA: 50 ppm (REL - (for up to a 10 hour work day))
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	TWA: 240 mg/m ³ (REL - (for up to a 10 hour work day))
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	IDLH: 1800 ppm (10% of LEL)
	Silica, crystalline quartz (respirable)	14808-60-7	REL-TWA: 0.05 mg/m ³ (respirable - up to 10 hr)
	Silica, crystalline quartz (respirable)	14808-60-7	IDLH: 50 mg/m ³ (respirable)
	Toluene	108-88-3	IDLH: 500 mg/m ³
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	Ceiling Limit: 1800 mg/m ³ (petroleum distillates [15 min])
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	REL-TWA: 350 mg/m ³ (petroleum distillates [up to 10 hr])
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 350 mg/m ³ (up to 10 hr [petroleum distillates, naphtha])
	Distillates (petroleum), hydrotreated light	64742-47-8	Ceiling Limit: 1800 mg/m ³ ([15 min] petroleum distillates, naphtha)
	Distillates (petroleum), hydrotreated light	64742-47-8	REL-TWA: 100 mg/m ³ (up to 10 hr [kerosene])
OSHA	Zirconium 2-Ethylhexanoate	22464-99-9	TWA: 5 mg/m ³ (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	PEL: 5 mg/m ³ (as Zr)
	Zirconium 2-Ethylhexanoate	22464-99-9	STEL: 10 mg/m ³ (as Zr)
	Toluene	108-88-3	8-Hour TWA: 200 ppm (Table Z-2)
	Toluene	108-88-3	Ceiling Limit: 300 ppm (Table Z-2)
	Toluene	108-88-3	Peak Exposure Limit Value: 500 ppm (for an 8 hr shift; duration: 10 minutes [Table Z-2])
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	8-Hour TWA-PEL: 2000 mg/m ³ (500 ppm [petroleum distillates] - A single TWA does not sufficiently cover this broad category. The concentration of benzene and other aromatic hydrocarbons should also be considered.)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 525 mg/m ³
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 100 ppm
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	8-Hour TWA-PEL: 50 ppm
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	8-Hour TWA-PEL: 240 mg/m ³
	Silica, crystalline quartz (respirable)	14808-60-7	8-Hour TWA-PEL: 0.05 mg/m ³ (respirable)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 8 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Toluene	108-88-3	TWA: 375 mg/m ³ (100 ppm; [Table Z-1-A])
	Toluene	108-88-3	STEL: 560 mg/m ³ (150 ppm; [Table Z-1-A])
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 2000 mg/m ³ (500 ppm [aliphatic hydrocarbons])
	Silica, crystalline quartz (respirable)	14808-60-7	8-Hour TWA-PEL: 0.025 mg/m ³ (Action level - respirable)
United States(California)	Toluene	108-88-3	8-Hour TWA-PEL: 37 mg/m ³ (10 ppm)
	Toluene	108-88-3	15-Minute STEL: 560 mg/m ³ (150 ppm)
	Toluene	108-88-3	Ceiling Limit: 500 ppm
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 525 mg/m ³
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	8-Hour TWA: 50 ppm (OSHA (California))
	2-Pentanone, 4-hydroxy-4-methyl-	123-42-2	8-Hour TWA: 240 mg/m ³ (OSHA (California))
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 1 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 4 mg/m ³
	Silica, crystalline quartz (respirable)	14808-60-7	8-Hour TWA-PEL: 0.05 mg/m ³ (respirable dust)
	Toluene	108-88-3	REL: 37000 ug/m ³ (Acute inhalation)
	Toluene	108-88-3	REL: 300 ug/m ³ (Chronic inhalation)
	Naphtha (petroleum), hydrotreated heavy	64742-48-9	8-Hour TWA-PEL: 1600 mg/m ³ (400 ppm [petroleum distillates] - A single TWA does not sufficiently cover this broad category. The concentration of benzene and other aromatic hydrocarbons should also be considered.)
	Distillates (petroleum), hydrotreated light	64742-47-8	8-Hour TWA-PEL: 1600 mg/m ³ (400 ppm [aliphatic hydrocarbons])
	Silica, crystalline quartz (respirable)	14808-60-7	REL: 3 ug/m ³ (chronic inhalation [respirable])
WEEL	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 10 ppm
	1-methyl-2-pyrrolidone	872-50-4	8-Hour TWA: 40 mg/m ³
	Methyl ethyl ketoxime	96-29-7	8-Hour TWA: 36 mg/m ³ (10 ppm)

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	1-methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N-methyl-2-pyrrolidone	Urine	End of shift	100 mg/L
	Toluene	108-88-3	Toluene	Blood	Prior to last shift of work week	0.02 mg/L

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 9 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
	Toluene	108-88-3	o-Cresol, with hydrolysis	Creatinine in urine	End of shift	0.3 mg/g
	Toluene	108-88-3	Toluene	Urine	End of shift	0.03 mg/L

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Liquid, Medium Brown
Odor	Mild
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point/range	155°C

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 10 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Flash point (closed cup)	>38°C
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	0.75-1.2%
Vapor pressure	N/A
Vapor density	N/A
Density	0.89 +/- .02 g/cc
Relative density	0.89 +/- .02
Solubilities	N/A
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Cobalt bis(2-ethylhexanoate)	oral	LD50 Rat: 3129 mg/kg
	dermal	LD50 Rat: >2000 mg/kg

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 11 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Name	Route	Result
Zirconium 2-Ethylhexanoate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Guinea pig: 6300 mg/kg
Toluene	oral	LD50 Rat: 5580 mg/kg
	dermal	LD50 Rabbit: 12,267 mg/kg
	inhalation	LC50 Rat: 25.7 mg/L (4 h [Vapor])
Stoddard Solvent with < 0.1% Benzene content	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 5.5 mg/L (4 h)
	dermal	LD50 Rabbit: >3000 mg/kg
Distillates (petroleum), hydrotreated light	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5.28 mg/L (4 hr [vapor])
Cashew nutshell liquid	dermal	LD50 Rat: 2000 mg/kg
1-methyl-2-pyrrolidone	oral	LD50 Rat: 4150 mg/kg
	inhalation	LC50 Rat: >5.1 mg/L (4 hours)
	dermal	LD50 Rat: >5000 mg/kg
2-Pentanone, 4-hydroxy-4-methyl-	dermal	LD50 rabbit: 13500 mg/kg
	oral	LD50 rat: 2520 mg/kg
Methyl ethyl ketoxime	oral	LD50 Rat: 2326 mg/kg
	dermal	LD50 Rabbit: > 1000 mg/kg
	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 100 mg/kg
	inhalation	LC50 Rat: > 4.83 mg/L (4 hr (vapor))
Naphtha (petroleum), hydrodesulfurized heavy	oral	LD50 Rat: > 5000 mg/kg
Naphtha (petroleum), hydrotreated heavy	oral	LD50 Rat: 4820 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5 mg/L (4 hr Aerosol)

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Toluene	Causes skin irritation.
Stoddard Solvent with < 0.1% Benzene content	Causes skin irritation.
Cashew nutshell liquid	Causes skin irritation
1-methyl-2-pyrrolidone	Causes skin irritation.
Methyl ethyl ketoxime	Causes skin irritation.
Zirconium 2-Ethylhexanoate	Causes skin irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 12 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Cashew nutshell liquid	Causes serious eye damage
1-methyl-2-pyrrolidone	Causes serious eye irritation.
2-Pentanone, 4-hydroxy-4-methyl-	Causes serious eye irritation
Methyl ethyl ketoxime	Causes serious eye damage.
Stoddard Solvent with < 0.1% Benzene content	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product Data:

No data available.

Substance Data:

Name	Result
Cobalt bis(2-ethylhexanoate)	May cause an allergic skin reaction.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Cashew nutshell liquid	May cause an allergic skin reaction.
Methyl ethyl ketoxime	May cause an allergic skin reaction.

Carcinogenicity

Assessment:

Suspected of causing cancer.

Product Data: No data available.

Substance Data:

Name	Species	Result
Naphtha (petroleum), hydrotreated heavy	Not applicable.	May cause cancer. Animals exposed to high levels of some petroleum products have developed liver and kidney tumors. Occupationally exposed people in the petroleum refining industry have an increased risk of skin cancer and leukemia.
Naphtha (petroleum), hydrodesulfurized heavy		May cause cancer.
Methyl ethyl ketoxime		May cause cancer.
Silica, crystalline quartz (respirable)		May cause cancer via inhalation.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 13 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Name	Classification
Toluene	Group 3
Silica, crystalline quartz (respirable)	Group 1
Naphtha (petroleum), hydrotreated heavy	Not Applicable
Distillates (petroleum), hydrotreated light	Not Applicable
Cobalt bis(2-ethylhexanoate)	Group 2B
Zirconium 2-Ethylhexanoate	Not Applicable
Stoddard Solvent with < 0.1% Benzene content	Not Applicable
1-methyl-2-pyrrolidone	Not Applicable
2-Pentanone, 4-hydroxy-4-methyl-	Not Applicable
Methyl ethyl ketoxime	Not Applicable
Naphtha (petroleum), hydrodesulfurized heavy	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz (respirable)	Known to be human carcinogens
Naphtha (petroleum), hydrotreated heavy	Not Applicable
Distillates (petroleum), hydrotreated light	Not Applicable
Cobalt bis(2-ethylhexanoate)	Not Applicable
Zirconium 2-Ethylhexanoate	Not Applicable
Toluene	Not Applicable
Stoddard Solvent with < 0.1% Benzene content	Not Applicable
1-methyl-2-pyrrolidone	Not Applicable
2-Pentanone, 4-hydroxy-4-methyl-	Not Applicable
Methyl ethyl ketoxime	Not Applicable
Naphtha (petroleum), hydrodesulfurized heavy	Not Applicable

OSHA Carcinogens:

Ingredient Name	CAS	OSHA Carcinogens Status
Silica, crystalline quartz (respirable)	14808-60-7	Yes

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 14 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

No data available.

Substance Data:

Name	Result
Naphtha (petroleum), hydrotreated heavy	May cause genetic defects.
Naphtha (petroleum), hydrodesulfurized heavy	May cause genetic defects.

Reproductive Toxicity

Assessment:

May damage fertility or the unborn child.

Product Data:

No data available.

Substance Data:

Name	Result
Zirconium 2-Ethylhexanoate	Suspected of damaging the unborn child (developmental toxicity) via oral exposure.
Toluene	Suspected of damaging the unborn child.
1-methyl-2-pyrrolidone	May damage fertility or the unborn child (developmental effects).

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

Name	Result
Toluene	May cause drowsiness or dizziness.
1-methyl-2-pyrrolidone	May cause respiratory irritation.
Methyl ethyl ketoxime	May cause drowsiness or dizziness. Causes damage to the respiratory tract.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Toluene	May cause damage to organs (central nervous system; kidneys; liver) through prolonged or repeated exposure. Exposure to the substance may increase noise-induced hearing loss.
Stoddard Solvent with < 0.1% Benzene content	Causes damage to the Central Nervous System through prolonged or repeated exposure via inhalation.
Silica, crystalline quartz (respirable)	Causes damage to organs (lungs; kidneys; immune system) through prolonged or repeated exposure via inhalation.
Naphtha (petroleum), hydrodesulfurized heavy	Causes damage to the central nervous system through prolonged or repeated exposure.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 15 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Name	Result
Methyl ethyl ketoxime	May cause damage to the blood system through prolonged or repeated exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Toluene	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated heavy	May be fatal if swallowed and enters airways.
Stoddard Solvent with < 0.1% Benzene content	May be fatal if swallowed and enters airways.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrodesulfurized heavy	May be fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Cobalt bis(2-ethylhexanoate)	Fish LC50 Onchorhynchus mykiss: 1.5 mg/L
Naphtha (petroleum), hydrotreated heavy	Fish LC50 Onchorhynchus mykiss: 10 mg/L (96 H)
	Aquatic Invertebrates EC50 Daphnia magna: 4.5 mg/L (48 H)
	Aquatic Plants EC50 Green Algae: 3.3 mg/L (72 H)
	Fish LC50 Pimephales promelas: 8.2 mg/L (96 H)
Stoddard Solvent with < 0.1% Benzene content	Fish LC50 Onchorhynchus mykiss: 0.14 mg/L (96 hours)
Distillates (petroleum), hydrotreated light	Fish LC50 Lepomis macrochirus: 2.2 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 1.4 mg/L (48 hr)
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 6.7 mg/L (72 hr)
1-methyl-2-pyrrolidone	Fish LC50 Onchorhynchus mykiss: 500 mg/L (96 hours)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 16 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Name	Result
Methyl ethyl ketoxime	Fish LC50 <i>Oryzias latipes</i> : > 100 mg/L (96 hr)
	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 201 mg/L (48 hr)
	Aquatic Plants EC50 <i>Scenedesmus capricornutum</i> : 6.09 mg/L (72 hr)
2-Pentanone, 4-hydroxy-4-methyl-	Fish LC50 <i>Oryzias latipes</i> : >100 mg/L (96 h)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Cobalt bis(2-ethylhexanoate)	Fish EC10 <i>Cyprinodon variegatus</i> : 31.8 mg/L
Stoddard Solvent with < 0.1% Benzene content	Fish NOEC <i>Oncorhynchus mykiss</i> : 0.02 mg/L (30 d)
1-methyl-2-pyrrolidone	Aquatic Invertebrates NOEC <i>Daphnia magna</i> : 12.5 mg/L (21 days)
Methyl ethyl ketoxime	Fish NOEC <i>Oryzias latipes</i> : 50 mg/L (14 d)
	Aquatic Invertebrates NOEC <i>Daphnia magna</i> : ≥ 100 mg/L (21 d)
	Aquatic Plants NOEC <i>Scenedesmus capricornutum</i> : 1.02 mg/L (72 hr)
Naphtha (petroleum), hydrotreated heavy	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 10 mg/L (21 days)
	Fish LC50 <i>Pimephales promelas</i> : 5.2 mg/L (14 days)
Distillates (petroleum), hydrotreated light	Aquatic Invertebrates EC50 <i>Daphnia magna</i> : 0.81 mg/L (21 d)
2-Pentanone, 4-hydroxy-4-methyl-	Aquatic Invertebrates NOEC <i>Daphnia magna</i> : 100 mg/L (21 d)

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Cobalt bis(2-ethylhexanoate)	Not readily biodegradable.
Zirconium 2-Ethylhexanoate	Readily biodegradable in water.
Toluene	Readily biodegradable in water.
Stoddard Solvent with < 0.1% Benzene content	Readily biodegradable.
1-methyl-2-pyrrolidone	The substance is readily biodegradable (73% degradation in 28 days).
Methyl ethyl ketoxime	Inherently biodegradable (70% degradation after 18 days).
Naphtha (petroleum), hydrodesulfurized heavy	Inherently biodegradable in water.
Distillates (petroleum), hydrotreated light	Substance is considered to be inherently biodegradable in water.
2-Pentanone, 4-hydroxy-4-methyl-	Readily biodegradable (100% degradation after 14 days).

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 17 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Name	Result
Toluene	BCF: 90
Stoddard Solvent with < 0.1% Benzene content	BCF: 39.66 L/Kg ww; Not considered to be bioaccumulative.
1-methyl-2-pyrrolidone	The substance has low potential for bioaccumulation (Log Kow: -0.38).
Methyl ethyl ketoxime	BCF: 5.8
Distillates (petroleum), hydrotreated light	This substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
2-Pentanone, 4-hydroxy-4-methyl-	The substance is not expected to bioaccumulate (Log Kow: -0.340).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Toluene	Moderately Mobile (Calculated Koc: 205)
Stoddard Solvent with < 0.1% Benzene content	Koc at 20°C: 1451
1-methyl-2-pyrrolidone	Adsorption to the solid soil phase is not expected.
Distillates (petroleum), hydrotreated light	This substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Stoddard Solvent with < 0.1% Benzene content	The substance is not PBT.
1-methyl-2-pyrrolidone	The substance is not PBT.
Methyl ethyl ketoxime	The substance is not PBT.
Naphtha (petroleum), hydrodesulfurized heavy	This substance is not PBT.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.
Naphtha (petroleum), hydrotreated heavy	The substance is not PBT.
2-Pentanone, 4-hydroxy-4-methyl-	The substance is not PBT.

vPvB assessment:

Stoddard Solvent with < 0.1% Benzene content	The substance is not vPvB.
1-methyl-2-pyrrolidone	The substance is not vPvB.
Methyl ethyl ketoxime	The substance is not vPvB.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 18 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

Naphtha (petroleum), hydrodesulfurized heavy	This substance is not vPvB.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.
Naphtha (petroleum), hydrotreated heavy	The substance is not vPvB.
2-Pentanone, 4-hydroxy-4-methyl-	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:


Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage. Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Contaminated packages:


Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN 1263, Combustible, No red label required
UN Proper Shipping Name	PAINT
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	PAINT
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	PAINT

Safety Data Sheet


According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 19 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

UN Transport Hazard Class(es)	3	
Packing Group	III	
Environmental Hazards	None	
Special Precautions for User	None	

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

108-88-3	Toluene	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed

CERCLA:

108-88-3	Toluene	Listed	1000 lb
64742-47-8	Distillates (petroleum), hydrotreated light	Listed	100 lb

RCRA:

108-88-3	Toluene	Listed	U220
64742-47-8	Distillates (petroleum), hydrotreated light	Listed	D001

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

108-88-3	Toluene	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
123-42-2	2-Pentanone, 4-hydroxy-4-methyl-	Listed
14808-60-7	Silica, crystalline quartz (respirable)	Listed

New Jersey Right to Know:

136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
123-42-2	2-Pentanone, 4-hydroxy-4-methyl-	Listed
14808-60-7	Silica, crystalline quartz (respirable)	Listed

New York Right to Know:

136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 04.20.2020

Page 20 of 20

Revision date: 12.28.2021

Absco Quick Dry Penetrating Wood Finish - Espresso

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
123-42-2	2-Pentanone, 4-hydroxy-4-methyl-	Listed

Pennsylvania Right to Know:

136-52-7	Cobalt bis(2-ethylhexanoate)	Listed
108-88-3	Toluene	Listed
64742-48-9	Naphtha (petroleum), hydrotreated heavy	Listed
8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed
872-50-4	1-methyl-2-pyrrolidone	Listed
123-42-2	2-Pentanone, 4-hydroxy-4-methyl-	Listed
14808-60-7	Silica, crystalline quartz (respirable)	Listed

California Proposition 65:

⚠️WARNING: This product can expose you to Silica, crystalline quartz (respirable); which is known to the State of California to cause cancer; and Toluene and 1-methyl-2-pyrrolidone, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Canlak Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Canlak Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 2-2-1

HMIS: 2*-2-1

Initial Preparation Date: 04.20.2020

Revision date: 12.28.2021

Revision Notes:

Revision Date	Notes
2020-05-06	Version 02
2021-12-28	Version 03

End of Safety Data Sheet