

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 1 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

SECTION 1: Identification

Product Identifier

Product Name: Absco Swedish Crown Matte

Product code: PR21200301

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Finishes, Coatings, and Related Materials

Uses Advised Against: Not determined or not applicable.

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Canlak Coatings

1999 Elizabeth Street

North Brunswick, New Jersey 089026316

(732)821-3200

<https://canlakcoatings.com>

Emergency Telephone Number:

United States

CHEMTREC

(703)527-3887 (24 HRS)

(800)424-9300

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin irritation, category 2

Serious eye damage, category 1

Flammable liquids, category 2

Corrosive to metals, category 1

Skin sensitization, category 1

Carcinogenicity, category 1B

Specific target organ toxicity - single exposure, category 1

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Pictograms:



Signal Word: Danger

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 2 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Hazard statements:

- H225 Highly flammable liquid and vapor
- H290 May be corrosive to metals
- H315 Causes skin irritation
- H318 Causes serious eye damage
- H317 May cause an allergic skin reaction
- H350 May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H370 Causes damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness

Precautionary Statements:

- P264 Wash skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P234 Keep only in original container
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P272 Contaminated work clothing must not be allowed out of the workplace
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P302+P352 IF ON SKIN: Wash with plenty of water/ ...
- P321 Specific treatment (see ... on this label)
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362 Take off contaminated clothing and wash it before reuse
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER/doctor/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P370+P378 In case of fire: Use ... to extinguish
- P390 Absorb spillage to prevent material-damage
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention
- P363 Wash contaminated clothing before reuse
- P308+P313 IF exposed or concerned: Get medical advice/attention
- P307+P311 IF exposed: Call a POISON CENTER or doctor/physician
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P312 Call a POISON CENTER/doctor/.../if you feel unwell
- P403+P235 Store in a well-ventilated place. Keep cool
- P406 Store in corrosive resistant/... container with a resistant inner liner
- P405 Store locked up
- P403+P233 Store in a well-ventilated place. Keep container tightly closed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 3 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

P501 Dispose of contents/container to...

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64-17-5	Ethanol	<50
CAS Number: 107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	<15
CAS Number: 71-36-3	n-Butanol	<13
CAS Number: 63148-65-2	Butvar B-98	<12
CAS Number: 67-56-1	Methanol	<8
CAS Number: 67-63-0	Propan-2-ol	<5
CAS Number: 109-60-4	Propyl acetate	<3
CAS Number: 108-10-1	4-Methylpentan-2-one	<2
CAS Number: 1330-20-7	Xylene	<3
CAS Number: 7664-38-2	Phosphoric Acid	<2
CAS Number: 50-00-0	Formaldehyde	<0.12

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 4 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Products that are corrosive to metals are often corrosive to the skin, eyes and the respiratory tract.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Causes damage to organs. Effects are dependent on exposure (dose, concentration, contact time).

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure may cause cancer. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

If exhibiting symptoms of exposure, seek prompt medical attention.

If respiratory symptoms persist, seek medical attention.

Overexposure via inhalation requires urgent medical treatment.

Skin/eye burns require immediate treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 5 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Contact with metals may evolve flammable hydrogen gas. Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

DO NOT GET WATER INSIDE CONTAINERS. Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 6 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable corrosive resistant containers for future disposal. Do not get water in containers as reaction with water or moist air may release toxic, corrosive or flammable gases. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 7 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10). Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Phosphoric Acid	7664-38-2	8-Hour TWA: 1 mg/m ³
	Phosphoric Acid	7664-38-2	15-Minute STEL: 3 mg/m ³
	n-Butanol	71-36-3	TLV-TWA: 20 ppm (8-Hour Exposure Limit)
	Xylene	1330-20-7	8-Hour TWA: 100 ppm
	Xylene	1330-20-7	15-Minute STEL: 150 ppm
	Formaldehyde	50-00-0	15-Minute STEL: 0.3 ppm
	Formaldehyde	50-00-0	8-Hour TWA: 0.1 ppm
	Propan-2-ol	67-63-0	15-Minute STEL: 400 ppm
	Propan-2-ol	67-63-0	8-Hour TWA: 200 ppm
	Ethanol	64-17-5	15-Minute STEL: 1000 ppm
	Methanol	67-56-1	8-Hour TWA: 200 ppm
	Methanol	67-56-1	15-Minute STEL: 250 ppm
	4-Methylpentan-2-one	108-10-1	TWA: 20 ppm
	4-Methylpentan-2-one	108-10-1	STEL: 75 ppm
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	TLV-TWA: 50 ppm (8 hr)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 100 ppm
	Propyl acetate	109-60-4	15-Minute STEL: 150 ppm
	Propyl acetate	109-60-4	TLV-TWA: 100 ppm (8 hr)
NIOSH	Phosphoric Acid	7664-38-2	REL-TWA: 1 mg/m ³ (up to 10 hr)
	Phosphoric Acid	7664-38-2	STEL: 3 mg/m ³
	Phosphoric Acid	7664-38-2	IDLH: 1000 mg/m ³
	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m ³)
	n-Butanol	71-36-3	IDLH: 1400 ppm
	Xylene	1330-20-7	REL-TWA: 435 mg/m ³ (100 ppm [up to 10 hr])
	Xylene	1330-20-7	15-Minute STEL: 655 mg/m ³ (150 ppm)
	Xylene	1330-20-7	IDLH: 900 ppm
	Formaldehyde	50-00-0	REL-TWA: 0.016 ppm (up to 10 hr)
	Formaldehyde	50-00-0	Ceiling Limit: 0.1 ppm (15 min)
	Formaldehyde	50-00-0	IDLH: 20 ppm

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 8 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Propan-2-ol	67-63-0	IDLH: 2000 ppm
	Propan-2-ol	67-63-0	15-Minute STEL: 500 ppm (1,225 mg/m ³)
	Propan-2-ol	67-63-0	REL-TWA: 400 ppm (980 mg/m ³ - up to 10 hrs.)
	Ethanol	64-17-5	REL-TWA: 1900 mg/m ³ (1000 ppm [up to 10 hr.])
	Ethanol	64-17-5	IDLH: 3300 ppm
	Methanol	67-56-1	REL-TWA: 260 mg/m ³ (200 ppm [for up to a 10-hour workday during a 40-hour workweek])
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	IDLH: 6000 ppm
	4-Methylpentan-2-one	108-10-1	TWA: 50 ppm (up to 10 hr.)
	4-Methylpentan-2-one	108-10-1	TWA: 205 mg/m ³ (up to 10 hr.)
	4-Methylpentan-2-one	108-10-1	15-Minute STEL: 75 ppm
	4-Methylpentan-2-one	108-10-1	15-Minute STEL: 300 mg/m ³
	4-Methylpentan-2-one	108-10-1	IDLH: 500 ppm
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	REL-TWA: 360 mg/m ³ (100 ppm [for up to a 10-hour workday during a 40-hour workweek])
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	STEL: 540 mg/m ³ (150 ppm)
	Propyl acetate	109-60-4	IDLH: 1700 ppm
	Propyl acetate	109-60-4	STEL: 1050 mg/m ³ (250 ppm)
	Propyl acetate	109-60-4	REL-TWA: 840 mg/m ³ (200 ppm [up to 10 hr])
OSHA	Phosphoric Acid	7664-38-2	8-Hour TWA-PEL: 1 mg/m ³ (Table Z-1)
	Phosphoric Acid	7664-38-2	TWA: 1 mg/m ³ (Table Z-1-A)
	Phosphoric Acid	7664-38-2	STEL: 3 mg/m ³ (Table Z-1-A)
	n-Butanol	71-36-3	8-Hour TWA-PEL: 100 ppm (300 mg/m ³)
	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m ³)
	Xylene	1330-20-7	8-Hour TWA-PEL: 435 mg/m ³ (100 ppm)
	Formaldehyde	50-00-0	8-Hour TWA-PEL: 0.75 ppm
	Formaldehyde	50-00-0	15-Minute STEL: 2 ppm
	Propan-2-ol	67-63-0	8-Hour TWA-PEL: 980 mg/m ³ (400 ppm)
	Ethanol	64-17-5	8-Hour TWA-PEL: 1900 mg/m ³ (1000 pm)
	Methanol	67-56-1	8-Hour TWA-PEL: 260 mg/m ³ (200 ppm)
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	4-Methylpentan-2-one	108-10-1	8-Hour TWA-PEL: 100 ppm
	4-Methylpentan-2-one	108-10-1	8-Hour TWA-PEL: 410 mg/m ³

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 9 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Formaldehyde	50-00-0	8-Hour TWA-PEL: 0.5 ppm (Action level)
	Propyl acetate	109-60-4	8-Hour TWA-PEL: 840 mg/m ³ (200 ppm)
	Propyl acetate	109-60-4	STEL: 1050 mg/m ³ (250 ppm)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	8-Hour TWA-PEL: 360 mg/m ³ (100 ppm)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 540 mg/m ³ (150 ppm)
United States(California)	Phosphoric Acid	7664-38-2	8-Hour TWA-PEL: 1 mg/m ³
	Phosphoric Acid	7664-38-2	15-Minute STEL: 3 mg/m ³
	Xylene	1330-20-7	8-Hour TWA-PEL: 435 mg/m ³ (100 ppm)
	Xylene	1330-20-7	15-Minute STEL: 635 mg/m ³ (150 ppm)
	Propan-2-ol	67-63-0	8-Hour TWA-PEL: 980 mg/m ³ (400 ppm - Cal/OSHA)
	Ethanol	64-17-5	8-Hour TWA-PEL: 1900 mg/m ³ (1000 ppm)
	Methanol	67-56-1	15-Minute STEL: 325 mg/m ³ (250 ppm)
	Methanol	67-56-1	PEL Ceiling: 1000 ppm
	Methanol	67-56-1	8-Hour TWA: 260 mg/m ³ (200 ppm)
	4-Methylpentan-2-one	108-10-1	8-Hour TWA-PEL: 205 mg/m ³ (Cal/OSHA)
	4-Methylpentan-2-one	108-10-1	15-Minute STEL: 300 mg/m ³ (Cal/OSHA)
	4-Methylpentan-2-one	108-10-1	8-Hour TWA-PEL: 205 mg/m ³ (Cal/OSHA)
	4-Methylpentan-2-one	108-10-1	15-Minute STEL: 75 ppm (Cal/OSHA)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	8-Hour TWA: 100 ppm (360 mg/m ³)
	1-methoxy-2-propanol monopropylene glycol methyl ether	107-98-2	15-Minute STEL: 150 ppm (540 mg/m ³)
	Phosphoric Acid	7664-38-2	REL: 7 ug/m ³ (8 hr; Chronic inhalation)
	n-Butanol	71-36-3	Ceiling Limit: 50 ppm (150 mg/m ³)
	Xylene	1330-20-7	PEL Ceiling: 300 ppm
	Formaldehyde	50-00-0	15-Minute STEL: 2 ppm
	Formaldehyde	50-00-0	8-Hour TWA-PEL: 0.75 ppm
	Formaldehyde	50-00-0	8-Hour TWA: 0.5 ppm (Action level)
	Propan-2-ol	67-63-0	REL: 3200 ug/m ³ (Acute Inhalation)
	Propan-2-ol	67-63-0	REL: 7000 ug/m ³ (Chronic Inhalation)
	Propyl acetate	109-60-4	PEL-STEEL: 1050 mg/m ³ (250 ppm [15 min])

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 10 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Propyl acetate	109-60-4	8-Hour TWA-PEL: 840 mg/m ³ (200 ppm)

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Methanol	67-56-1	Methanol	Urine	End of Shift	15 mg/L
	4-Methylpentan-2-one	108-10-1	Methyl isobutyl ketone	Urine	End of shift	1 mg/L
	Xylene	1330-20-7	Methylhippuric acids	Creatinine in urine	End of shift.	1.5 g/g
	Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work week	40 mg/L
	Methanol	67-56-1	Methanol	Urine	End of shift.	15 mg/L

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection.

Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 11 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Hazy liquid
Odor	Solvent
Odor threshold	N/A
pH	N/A
Melting point/freezing point	N/A
Initial boiling point/range	78.3° C
Flash point (closed cup)	>10° C
Evaporation rate	Faster than water
Flammability (solid, gas)	LFL = 1.1-1.3% by volume
Upper flammability/explosive limit	N/A
Lower flammability/explosive limit	N/A
Vapor pressure	N/A
Vapor density	Heavier than air
Density	0.87 +/-0.02 g/cc
Relative density	0.87 +/-0.02
Solubilities	N/A
Partition coefficient (n-octanol/water)	N/A
Auto/Self-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidizing properties	N/A

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 12 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Phosphoric Acid	inhalation	LC50 Rat: > 850 mg/m ³ (1 hr)
	oral	LD50 Rat: 1530 mg/kg
	dermal	LD50 Rabbit: 2740 mg/kg
n-Butanol	oral	LD50 Rat: 790 mg/kg
	dermal	LD50 Rabbit: 3400 mg/kg
Xylene	dermal	LD50 Rabbit: 1700 mg/kg
	inhalation	LC50 Rat: 5100 ppmV (4 h)
	oral	LD50 Rat: 3523 mg/kg
Formaldehyde	oral	LD50 Rat: 100 mg/kg
	inhalation	LC50 Rat: <463 ppmV (4 hr (vapor))
	dermal	LD50 Rabbit: 270 mg/kg
Propan-2-ol	oral	LD50 Rat: 5840 mg/kg
	dermal	LD50 Rabbit: 12,800 mg/kg
	inhalation	LC50 Rat: 72.6 mg/L (4 hr - Vapor)
Ethanol	oral	LD50 Rat: 6,200 mg/kg
	inhalation	LC50 Rat: 116.9 mg/L (4 hr [Vapor])
	dermal	LD50 Rabbit: 17,100 mg/kg
Propyl acetate	oral	LD50 Rat: 8700 mg/kg
	dermal	LD50 Rabbit: > 17,800 mg/kg
	inhalation	LC50 Rat: 32 mg/L (4 hr [vapor])
4-Methylpentan-2-one	inhalation	LC50 Mouse: 5688 ppmV
		LC50 Rat: 100,000 mg/m ³
	oral	LD50 Rat: 2080 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 13 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Name	Route	Result
1-methoxy-2-propanol monopropylene glycol methyl ether	oral	LD50 Rat: 3739 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
Methanol	Oral ATE	LD50 Rat: 100 mg/kg
	Dermal ATE	LD50 Rabbit: 300 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr)
	oral	LD50 Rat: 5628 mg/kg
	dermal	LD50 Rabbit: 15,800 mg/kg
	inhalation	LC50 Rat: 64,000 ppmV (4 hr)

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Phosphoric Acid	Causes severe skin burns.
n-Butanol	Causes skin irritation.
Xylene	Causes skin irritation.
Formaldehyde	Causes severe skin burns.
Butvar B-98	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Phosphoric Acid	Causes serious eye damage.
n-Butanol	Causes serious eye damage.
Formaldehyde	Causes serious eye damage.
Propan-2-ol	Causes serious eye irritation.
Propyl acetate	Causes serious eye irritation.
4-Methylpentan-2-one	Causes serious eye irritation.
Butvar B-98	Causes serious eye irritation.
Ethanol	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 14 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Name	Result
Formaldehyde	May cause an allergic skin reaction.

Carcinogenicity

Assessment:

May cause cancer.

Product Data: No data available.

Substance Data:

Name	Species	Result
Formaldehyde		May cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Formaldehyde	Group 1
Propan-2-ol	Group 3
Ethanol	Not Applicable
4-Methylpentan-2-one	Group 2B
Phosphoric Acid	Not Applicable
n-Butanol	Not Applicable
Xylene	Group 3
Methanol	Not Applicable
Propyl acetate	Not Applicable
1-methoxy-2-propanol monopropylene glycol methyl ether	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Formaldehyde	Known to be human carcinogens
Propan-2-ol	Not Applicable
Ethanol	Not Applicable
4-Methylpentan-2-one	Not Applicable
Phosphoric Acid	Not Applicable
n-Butanol	Not Applicable
Xylene	Not Applicable
Methanol	Not Applicable
Propyl acetate	Not Applicable
1-methoxy-2-propanol monopropylene glycol methyl ether	Not Applicable

OSHA Carcinogens:

Ingredient Name	CAS	OSHA Carcinogens Status
Formaldehyde	50-00-0	Yes

Germ Cell Mutagenicity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 15 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Formaldehyde	Suspected of causing genetic defects.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

- Causes damage to organs.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data:

Name	Result
n-Butanol	May cause drowsiness or dizziness
	May cause respiratory irritation.
Propan-2-ol	May cause drowsiness or dizziness.
Methanol	Causes damage to Optic nerve (nervus opticus), central nervous system.
Propyl acetate	May cause drowsiness or dizziness via inhalation.
4-Methylpentan-2-one	May cause respiratory irritation.
1-methoxy-2-propanol monopropylene glycol methyl ether	May cause drowsiness or dizziness.
Butvar B-98	May cause respiratory irritation.
Formaldehyde	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Phosphoric Acid	Repeated and/or prolonged exposure may have effects on the upper respiratory tract and lungs. This may result in chronic inflammation and reduced lung function.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 16 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	Aquatic Plants EC50 Green algae: 225 mg/L (96 Hours)
	Aquatic Invertebrates EC50 Daphnia magna: 1328 mg/L (48 Hours)
	Fish LC50 Pimephales promelas: 1376 mg/L (96 Hours)
4-Methylpentan-2-one	Fish LC50 Danio rerio: \geq 179 mg/L (96h)
Phosphoric Acid	Aquatic Invertebrates EC50 Daphnia magna: $>$ 100 mg/L (48 hr)
	Aquatic Plants EC50 Desmodosmus subspicatus: $>$ 100 mg/L (72 hr)
Xylene	Fish LC50 Freshwater fish: 2.6 mg/L (96 h)
	Aquatic Invertebrates EC50 Daphnia magna: 1.8 mg/L (48 h)
	Aquatic Plants EC50 Freshwater algae: 3.2 mg/L (72 h)
Ethanol	Fish LC50 Alburnus alburnus: 11,000 mg/L (96 h)
	Aquatic Invertebrates EC50 Daphnia magna: $>$ 10,000 mg/L (48 h)
	Aquatic Plants EC50 Chlorella vulgaris: 275 mg/L (72 h)
	Bacteria LC50 Paramaecium caudatum: 5800 mg/L (4 h)
Propyl acetate	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 672 mg/L (72 hr)
	Fish LC50 Pimephales promelas: 60 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 91.5 mg/L (48 hr)
1-methoxy-2-propanol monopropylene glycol methyl ether	Fish LC50 Leuciscus idus: 6812 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 23300 mg/L (48 hr)
	Aquatic Plants EC50 Desmodosmus subspicatus: $>$ 500 mg/L (72 hr)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	Aquatic Invertebrates NOEC Daphnia magna: 4.1 mg/L (21 Days)
4-Methylpentan-2-one	Aquatic Invertebrates NOEC Daphnia magna: 30-35 mg/L (21d)
Xylene	Fish NOEC Salmo gairdneri: $>$ 1.3 mg/L (56 d)
	Aquatic Invertebrates NOEC Ceriodaphnia dubia: 0.96 mg/L (7 d)

Persistence and Degradability

Product Data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 17 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Substance Data:

Name	Result
n-Butanol	The substance is readily biodegradable (> 92% degradation in 28 days).
Xylene	Readily biodegradable in water.
Formaldehyde	Readily biodegradable (99% degradation after 28 days).
Propan-2-ol	Readily biodegradable in water.
Ethanol	Readily biodegradable in water (74% after 5 days).
Methanol	Readily biodegradable (97% degradation after 20 days).
Propyl acetate	Readily biodegradable in water (62% degradation [O2 consumption] in 5 days).
4-Methylpentan-2-one	The substance is concluded to be readily biodegradable.
1-methoxy-2-propanol monopropylene glycol methyl ether	This substance is readily biodegradable in water (96% degradation after 28 days).

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	The substance is not expected to bioaccumulate (BCF: 3.16 L/Kg).
Xylene	BCF: >8.1 - <25.9
Formaldehyde	Accumulation in aquatic organisms is not to be expected.
Ethanol	Not expected to bioaccumulate (log Kow = -0.31).
Methanol	Methanol does not significantly bioaccumulate in fish. Experimental BCFs of < 10 in fish species.
Propyl acetate	Substance is not expected to bioaccumulate (log Kow: 1.24; estimated BCF: 3.76).
4-Methylpentan-2-one	No potential for bioaccumulation.
Propan-2-ol	Not expected to bioaccumulate (log Kow: 0.05).
4-Methylpentan-2-one	Log Kow: 1.31
1-methoxy-2-propanol monopropylene glycol methyl ether	Accumulation in organisms is not to be expected (estimated BCF: 3).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
n-Butanol	The substance is highly mobile (Log Koc: 0.54).
Xylene	Moderately Mobile (Log Koc: 2.73)
Formaldehyde	Adsorption to solid soil phase is possible.
Ethanol	Very high mobility in soil (Koc = 1).
Methanol	Highly mobile (Koc: 0.13 - 0.61 dimensionless).
Propyl acetate	Substance is expected to be mobile; therefore, adsorption to soil is not expected (calculated log Koc: 1.008).

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 18 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Name	Result
1-methoxy-2-propanol monopropylene glycol methyl ether	This substance is highly mobile; therefore, adsorption to soil is not expected (Koc: 5.93 L/kg).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Formaldehyde	Not a PBT substance.
Propan-2-ol	This substance is not PBT.
Ethanol	The substance is not PBT.
Methanol	This substance is not PBT.
Propyl acetate	This substance is not PBT.
4-Methylpentan-2-one	The substance is not PBT.
Phosphoric Acid	The PBT assessment does not apply to inorganic substances.
n-Butanol	The substance is not PBT.
Xylene	The substance is not PBT.
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is not PBT.

vPvB assessment:

Formaldehyde	Not a vPvB substance.
Propan-2-ol	This substance is not vPvB.
Ethanol	The substance is not vPvB.
Methanol	This substance is not vPvB.
Propyl acetate	This substance is not vPvB.
4-Methylpentan-2-one	The substance is not vPvB.
Phosphoric Acid	The vPvB assessment does not apply to inorganic substances.
n-Butanol	The substance is not vPvB.
Xylene	The substance is not vPvB.
1-methoxy-2-propanol monopropylene glycol methyl ether	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

Dispose of in accordance with local, state, and federal laws and regulations. Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Do not dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.

Contaminated packages:

Not determined or not applicable.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020


Page 19 of 22

Revision date: 12.30.2021


Absco Swedish Crown Matte

SECTION 14: Transport Information


United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN1263
UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	UN1263
UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	UN1263
UN Proper Shipping Name	Paint
UN Transport Hazard Class(es)	3 
Packing Group	III
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances:

50-00-0	Formaldehyde	Listed
---------	--------------	--------

SARA Section 313 Toxic Chemicals:

7664-38-2	Phosphoric Acid	Listed
71-36-3	n-Butanol	Listed
1330-20-7	Xylene	Listed
50-00-0	Formaldehyde	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 20 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

67-63-0	Propan-2-ol	Listed
67-56-1	Methanol	Listed
108-10-1	4-Methylpentan-2-one	Listed

CERCLA:

7664-38-2	Phosphoric Acid	Listed	5000 lb
71-36-3	n-Butanol	Listed	5000
1330-20-7	Xylene	Listed	100 lb
50-00-0	Formaldehyde	Listed	100 lb
64-17-5	Ethanol	Listed	100 lb
67-56-1	Methanol	Listed	5000 lbs
108-10-1	4-Methylpentan-2-one	Listed	5000 lb
109-60-4	Propyl acetate	Listed	100 lb

RCRA:

71-36-3	n-Butanol	Listed	U031
1330-20-7	Xylene	Listed	U239
50-00-0	Formaldehyde	Listed	U122
64-17-5	Ethanol	Listed	D001
67-56-1	Methanol	Listed	U154
108-10-1	4-Methylpentan-2-one	Listed	U161
109-60-4	Propyl acetate	Listed	D001

Section 112(r) of the Clean Air Act (CAA):

50-00-0	Formaldehyde	Listed
---------	--------------	--------

Massachusetts Right to Know:

7664-38-2	Phosphoric Acid	Listed
71-36-3	n-Butanol	Listed
50-00-0	Formaldehyde	Listed
67-63-0	Propan-2-ol	Listed
64-17-5	Ethanol	Listed
108-10-1	4-Methylpentan-2-one	Listed
107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
1330-20-7	Xylene	Listed
67-56-1	Methanol	Listed
109-60-4	Propyl acetate	Listed

New Jersey Right to Know:

7664-38-2	Phosphoric Acid	Listed
71-36-3	n-Butanol	Listed
50-00-0	Formaldehyde	Listed
67-63-0	Propan-2-ol	Listed
64-17-5	Ethanol	Listed
108-10-1	4-Methylpentan-2-one	Listed
107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
1330-20-7	Xylene	Listed

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 21 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

67-56-1	Methanol	Listed
109-60-4	Propyl acetate	Listed

New York Right to Know:

7664-38-2	Phosphoric Acid	Listed
71-36-3	n-Butanol	Listed
50-00-0	Formaldehyde	Listed
67-63-0	Propan-2-ol	Listed
64-17-5	Ethanol	Listed
108-10-1	4-Methylpentan-2-one	Listed
107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
1330-20-7	Xylene	Listed
67-56-1	Methanol	Listed
109-60-4	Propyl acetate	Listed

Pennsylvania Right to Know:

7664-38-2	Phosphoric Acid	Listed
71-36-3	n-Butanol	Listed
50-00-0	Formaldehyde	Listed
67-63-0	Propan-2-ol	Listed
64-17-5	Ethanol	Listed
108-10-1	4-Methylpentan-2-one	Listed
107-98-2	1-methoxy-2-propanol monopropylene glycol methyl ether	Listed
1330-20-7	Xylene	Listed
67-56-1	Methanol	Listed
109-60-4	Propyl acetate	Listed

California Proposition 65:

⚠ WARNING: This product can expose you to Formaldehyde; which is known to the State of California to cause cancer; and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

⚠ WARNING: This product can expose you to 4-Methylpentan-2-one; which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Canlak Coatings assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Canlak Coatings assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

NFPA: 3-3-1

HMIS: 3*-3-1

Initial Preparation Date: 05.13.2020

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.13.2020

Page 22 of 22

Revision date: 12.30.2021

Absco Swedish Crown Matte

Revision date: 12.30.2021

Revision Notes:

Revision Date	Notes
2020-05-06	Version 02
2021-12-30	Version 03

End of Safety Data Sheet