



FROM THE MAKER



POLYURETHANE FLOOR FINISH

PRO
SELECT
POLYURETHANE FLOOR FINISH

SPECIFICATIONS

VOC.	<500 g/L
Solids.	43%
Flash Point.	>100° F
Solvents.	Mineral Spirits
Shelf Life	1 Year Unopened
Coverage	500 sq. ft/gal
Color	Amber

FEATURES

- Excellent Adhesion, Flow, Leveling and Flexibility
- Compatible with most applicators, including roller, lambswool, brush and T-bar
- Easy application, apply with ¼" nap roller
- Dries in about 4 - 6 hours, recoat after 8 - 12 hours (varies with conditions and air flow)
- Resistant to abrasion, staining, scuffing, chipping, spills and perspiration
- Low-ambering finish with non-offensive odor
- Shelf-life 1-year, unopened container

PROFESSIONAL POLYURETHANE CLEAR FLOOR FINISH FOR ALL HARDWOODS

ABSCO is the #1 choice for high quality floor finishes for wood. Manufactured from the highest quality ingredients available today, PRO SELECT will provide many years of beauty and durability on all wood floor applications. PRO SELECT applies easily, leaving a beautiful "like new" finish. Ideal for new installation, stained wood, screen and recoat jobs or natural wood.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NFWA or NOFMA accepted manner. Remove dust completely by sweeping, vacuuming, and wiping the floor with a lint free cloth lightly dampened with mineral spirits. The floor, room and product temperature should be at least 65 degrees F. Do not apply over floors previously coated with wax, lacquer, shellac or stains containing stearates without complete removal of these substrates.

AVAILABLE IN: GLOSS, SEMI-GLOSS, AND SATIN FINISHES in one- and five-gallon containers only.