



PROFESSIONAL POLYURETHANE 350 VOC WOOD FLOOR FINISH



SPECIFICATIONS:

VOC.....	350 g/L
Solids.....	56% - 58%
Flash Point.....	> 101°F (> 38°C)
Solvent	Mineral Spirits
Viscosity.....	130 - 230 cps
Odor	Solvent Like
Coverage.....	500 - 600 sq. ft/gal
Dry Time:.....	3 - 6 Hours
Color (Wet).....	Dark Amber
Color (Dry).....	Amber Clear
Sheens.....	Super High Gloss, Semi-Gloss, Satin, Matte
Sizes	1g & 5g Containers

FEATURES

- Great Coverage & Low Odor
- Beautifies and Protects
- 350 VOC Formulation
- High Solids
- Commercial and Residential Use

Find us in

MasterSpec[®]

a product of The American Institute of Architects



PROVEN QUALITY AND VALUE WITH CONSISTENT RESULTS

Absco Professional Polyurethane Wood Floor Finish makes it easy, with great coverage, easy application and multiple VOC formulations. Its oil-modified high solids formulation is durable, self-leveling and is formulated for beauty and protection. And this 350 VOC formula is designed for residential and commercial use.

Please refer to the product label for specific surface preparation and application instructions.



ABSOLUTECOATINGS.COM

OFFICE (800) 432-4333 | FAX (732) 821-8180

1999 Elizabeth Street • North Brunswick, NJ 08902