



# SOLO CLEAR WOOD FLOOR FINISH



## SPECIFICATIONS:

VOC .....	275 g/L
Solids .....	30% (+/- 1% varies by sheen)
Flash Point .....	>100° C or >212° F
Solvent .....	Water
Viscosity .....	40 - 80 cps (60 - 100 for Matte)
Odor .....	Low Odor
Coverage .....	500 - 600 sq. ft/gal (Varies with Surface Porosity)
Dry Time .....	1 - 3 Hours
Color .....	Milky (When Wet)
Sheens .....	Satin & Matte
Sizes .....	1g & 5g Containers

## FEATURES

- Easy Application
- Roller & T-Bar Application
- Crystal Clear / Non-Yellowing
- Low Odor and Low VOC
- Good Build and Film Clarity When Dry

Find us in

**MasterSpec**<sup>®</sup>

a product of The American Institute of Architects



## A CRYSTAL CLEAR, FAST-DRYING WOOD FINISH THAT'S EASY TO USE

ABSCO SOLO CLEAR Wood Floor Finish is a non-yellowing waterborne urethane finish. It is easy to apply and abrade while providing very good adhesion with rapid dry times, allowing for multiple coats in one day to get the job done faster. Solo Clear can be used as a base and topcoat delivering a durable finish that is scuff- and-chemical resistant. Solo Clear includes all the key elements for treating and protecting wooden floors from start to finish!

**Please refer to the product label for specific surface preparation and application instructions.**



**ABSOLUTECOATINGS.COM**

OFFICE (800) 432-4333 | FAX (732) 821-8180

1999 Elizabeth Street • North Brunswick, NJ 08902