



PLATINUM 2K WOOD FLOOR FINISH



SPECIFICATIONS:

VOC.....	<275 g/L
Solids.....	32%
Flash Point.....	>200°
Solvent	Water/Glycol Ether
Viscosity.....	90 cps
Odor	Mild, Non Objectionable
Coverage.....	400 - 500 sq. ft/gal
Dry Time.....	2 - 3 Hours For Recoat
Cure Time	Full Cure In 72 Hours
Color (Wet).....	Whitish Emulsion
Color (Dry).....	Clear
Gloss Level (60%)	
.....	87 Minimum For Gloss
.....	25-35 For Semi Gloss
.....	10-20 For Satin
.....	5-10 For Matte
Sheens.....	Gloss, Semi-Gloss, Satin, Matte
Sizes	1g Container

FEATURES

- Once Catalyzed, Can Be Used Up To One Week
- Exceptional Durability
- Excellent Scratch & Stain Resistance
- 2K Performance With 1K Ease!
- Available In 4 Sheens
- No Isocyanate/No Aziridine
- Compliant Nationally
- Water Cleanup

EXCEPTIONAL DURABILITY IN AN EASY TO USE FORMULA

NEW! Absco Platinum 2K Wood Floor Finish is a high-performing 2K wood floor finish with the ease of a 1K. With a remarkably long open-time, exceptional durability, and excellent scratch and stain resistance, Platinum 2K is the perfect product for professionals and contractors who demand ease-of-use and fast return to service times. Platinum 2K uses no isocyanate or aziridine catalyst, and is nationally VOC compliant with easy water cleanup. Absco Grand Nxtgen TRS Sealer is recommended for use with Absco Platinum 2K.

Please refer to the product label for specific surface preparation and application instructions.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.