



GRAND NXTGEN

WOOD FLOOR FINISH



SPECIFICATIONS:

VOC.....	<275 g/L
Solids.....	29% - 31%
Flash Point.....	>100° C or >212° F
Solvent	Water
Viscosity.....	40 - 80 cps
Odor	Low Odor
Coverage.....	500 - 550 sq. ft/gal
Dry Time.....	1 - 3 Hours
Color	Slightly Amber
Sheens.....	Gloss, Semi-Gloss, Satin
Sizes	1g & 5g Containers

FEATURES

- NXTGEN Resins Deliver Greater Performance
- Increased Scuff Resistance
- Easy Application
- Enhanced Flow & Leveling
- Dry Time In 1 -3 Hours
- Great Coverage & Low Odor

PROFESSIONAL WOOD FINISH, AND THE NEXT GENERATION OF OIL MODIFIED URETHANE FOR ALL HARDWOODS

Introducing Absco Grand NXTGEN Wood Floor Finish, with technology driven resins for the next great advancement in waterborne finishes. Delivering the beautiful appearance and durability of an oil finish, Absco Grand NXTGEN uses a new innovative resin (next generation) to increase the performance you count on, with ease of application. Absco Grand NXTGEN is VOC compliant nationally and provides enhanced leveling, increased scuff resistance, excellent build/coverage, and low odor.

Please refer to the product label for specific surface preparation and application instructions.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.



GRAND NXTGEN

WOOD FLOOR FINISH

SURFACE PREPARATION: NEW OR NEWLY SANDED FLOORS: 1. Prepare the floor in the NWFA/NOFMA recommended manner. 2. Final cut before application of stain* should be with #80 grit paper and #120 screen disc. 3. Final cut before finish application on natural floor should be with #100 grit paper and #150 grit screen. 4. Vacuum well and remove all dust. *ABSCO GRAND NXTGEN should adhere well to most stains, but a test for adhesion over the stain is recommended.

APPLICATION OVER STAIN: We recommend Absco Quick Dry Penetrating Wood Finish Stain, following instructions on label until desired color is achieved. Allow stain sufficient time to dry, test with a dry cloth. Make sure the stain is completely dry before applying waterborne finish. It is always recommended to make a sample of the stain and topcoat, to ensure desired results.

PREVIOUSLY SEALED OR REFINISHED WOOD FLOORS: All wax, grease, soaps, oils and soil must be removed completely. Clean floor with a Wood Floor Cleaner. Screen floor with a 150-grit disc. Do not over-sand between coats. Make sure the floor is uniformly dull. Vacuum and wipe floor with cloth slightly dampened with water to remove all dust. **Equipment:** Apply with good quality nylon brush, pad or t-bar applicator. **Clean Up:** Use warm water to clean brushes and applicator. Coverage: 500-550 square feet per gallon.

RECOMMENDED SYSTEM ON RAW WOOD: For light traffic applications, minimum of 3 coats of ABSCO GRAND NXTGEN, or 1 coat Sealer (optional) and 2 coats of ABSCO GRAND NXTGEN. For high traffic areas, and soft or porous wood, minimum of 4 coats recommended. Test for adhesion prior to application on exotic or unusual species of wood, and woods containing oils.

APPLICATION: (Stir well before and during use.) Slightly dampen applicator with finish prior to starting. 1. Apply finish with the grain of the wood. 2. Pour finish onto floor in a 4" strip along the starting wall. 3. Pull the applicator towards you at a slight "snowplow" angle. Remember to keep a wet edge as you work. Feather all turns and stops in the direction which the applicator was pulled. 4. When you reach the end wall, pull the applicator around in a sweeping motion, without lifting it from the floor. 5. Feather turn, and gently touch any missed spots. 6. Apply at recommended coverage in thin coats. **DRYING TIME:** ABSCO GRAND NXTGEN will dry quickly, but please allow a min. of 2 hours drying between coats and good ventilation. No more than two coats of ABSCO GRAND NXTGEN per day are recommended. **RE-COATING:** Use a surface preparation system and a between coat abrasive pad system for multiple coats. **MAINTENANCE:** We recommend using a cleaning product for all polyurethane surfaces that is soap-free, no rinse formula, which will not harm polyurethane or varnished wood surfaces.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: May be harmful if swallowed. Causes skin irritation and serious eye irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Suspected of damaging fertility or the unborn child. Do not breathe vapors, spray mist, dust or chips from sanding. Avoid contact with skin, eyes or clothing. While spraying paint, or sanding surface, wear a mask or pesticide respirator approved by the National Institute for Occupational Safety and Health. Wear protective clothing (long sleeved cotton shirt, long pants, hat, gloves (such as nitril or butyl). Shoes and socks. Wash thoroughly with soap and water after handling and before eating, drinking, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse. Use in well-ventilated area.

Follow manufacturers instructions for cleaning/maintaining Personal Protection Equipment (PPE). If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advices.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Never give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately; wash with soap and water. Rinse with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor immediately for further treatment advice. For additional information in case of emergency call toll free Chemtrec - 1-800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

PHYSICAL AND CHEMICAL HAZARDS (STORAGE)

Store locked up and well-ventilated area.

WARNING: This product can expose you to chemicals including 2-methoxyethanol and 2-ethoxyethanol. Which is known to the state of California to cause birth defects or other reproductive Harm - www.P65Warnings.ca.gov.

KEEP FROM FREEZING. DO NOT THIN.

Spill: Absorb with inert and dispose of as specified under "Clean Up".

Clean Up: Soap and Water.

Disposal: Empty containers may retain residue. Follow label warnings even after the container is emptied. To dispose of contaminated absorbent, container and unused contents contact your sanitation department or State-designated environmental agency.

Refer to Safety Data Sheet for additional health and safety information.

KEEP OUT OF REACH OF CHILDREN

INGREDIENTS: Urethane polymer (Proprietary), Water (7732-18-5), Di (Propylene glycol) Butyl Ether (29911-28-2), 2-Ethylhexanoic acid, manganese salt (15956-58-8).

FACTORS BEYOND OUR CONTROL PREVENT US FROM ASSUMING RESPONSIBILITY FOR DAMAGE TO PROPERTY OR PERSON, EVEN WHEN THIS PRODUCT IS APPLIED ACCORDING TO DIRECTIONS. IN NO EVENT SHALL OUR LIABILITY EXCEED THE PURCHASE PRICE HEREOF.

THIS PRODUCT HAS A MAXIMUM VOC OF 275 g/L.

FOR WOOD SUBSTRATES ONLY

Item Number	Description	Size	Number per Case	Weight per Case
99001	Absco Grand Nxtgen - Gloss	GL	4	48 lbs.
99005	Absco Grand Nxtgen - Gloss	5G	N/A	38 lbs.
99101	Absco Grand Nxtgen - Satin	GL	4	48 lbs.
99105	Absco Grand Nxtgen - Satin	5G	N/A	38 lbs.
99201	Absco Grand Nxtgen - Semi-Gloss	GL	4	48 lbs.
99205	Absco Grand Nxtgen - Semi-Gloss	5G	N/A	38 lbs.



THIS IS **CANLAK COATINGS**

To find out more about our innovative line of coatings, visit canlakcoatings.com or call us at **800-432-4333**.